



Guy Adaptor for Multi Helix Screw Anchor

- Guy Adaptors are forgings used to engage the 1½" square shank of the Extension for Multi Helix Screw Anchor and accept guy wires in its' Multi-Strand Eye.
- Guy Adaptors are hot dip galvanized to meet ASTM Specification A153 Class C.


PART NUMBER	LENGTH	STD PKG
3566	Double Strand Adaptor	1
3567	Triple Strand Adaptor	1



No Wrench Screw Anchor

- Used for guying wires at utility poles.
- Anchors are installed by simply turning anchor into ground. No Wrench Anchors may be driven by hand or with power equipment.
- Eye dimensions are the same as Anchor Rods.
- Screw anchors consist of an unthreaded triple eye rod with an angled point, and a firmly welded helix.
- Hot dip galvanized to meet ASTM Specification A153, Class C.

PART NUMBER	HELIX DIAMETER	HELIX THICKNESS	ROD SIZE	STD PKG
6044	4"	3/16"	3/4" x 54"	1
1166	6"	1/4"	3/4" x 66"	1
1167	8"	1/4"	1" x 66"	1
1168	10"	1/4"	1 1/4" x 66"	1
1169	10"	1/4"	1 1/4" x 96"	1
1163	15"	1/2"	1 1/4" x 96"	1



Expanding Rock Anchor

- Used as a heavy-duty anchor in solid rock.
- Anchor consists of two Malleable castings that are asphaltum dipped and a hot dip galvanized Triple Eye Anchor Rod.
- Rod is hot dip galvanized to meet ASTM Specification A153, Class C.
- To install anchor, drill a 12" deep hole in solid rock, put anchor in hole, turn rod until anchor expands and wedges in the hole.
- The harder the pull on the rod, the tighter it wedges into the rock.

PART NUMBER	ROD DIAMETER	ROD LENGTH	ANCHOR SIZE	ANCHOR SIZE EXPANDED	HOLE SIZE	STD PKG
55500	3/4"	15"	1 3/4"	2 3/8"	1 7/8"	1
55501	3/4"	30"	1 3/4"	2 3/8"	1 7/8"	1
55502	3/4"	53"	1 3/4"	2 3/8"	1 7/8"	1
55503	3/4"	60"	1 3/4"	2 3/8"	1 7/8"	1
55504	3/4"	72"	1 3/4"	2 3/8"	1 7/8"	1
55505	3/4"	84"	1 3/4"	2 3/8"	1 7/8"	1
55506	3/4"	96"	1 3/4"	2 3/8"	1 7/8"	1
55508	1"	30"	2 1/4"	3 1/8"	2 3/8"	1
55509	1"	53"	2 1/4"	3 1/8"	2 3/8"	1
55510	1"	72"	2 1/4"	3 1/8"	2 3/8"	1
55511	1"	84"	2 1/4"	3 1/8"	2 3/8"	1
55512	1"	96"	2 1/4"	3 1/8"	2 3/8"	1