



Power Driven Anchors

SOLID SQUARE HUB SINGLE HELIX POWER DRIVEN ANCHOR

1-3/8" SQ. SOLID HUB: 4000 FT. LB. MAXIMUM WORKING TORQUE



PART#	DESCRIPTION	PKG QTY	CTN QTY	CTN WT.
3403	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 5/8" RODS - 4000 FT. LB.	6	1	62
3404	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 4000 FT. LB.	6	1	62
3405	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 5/8" RODS - 4000 FT. LB.	4	1	50
3406	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 4000 FT. LB.	4	1	54
3407	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB 4000LB FOR 5/8" RODS - 4000 FT. LB.	2	1	34
3408	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 4000 FT. LB.	2	1	34

1-3/8" SQ. SOLID HUB: 6000 FT. LB. MAXIMUM WORKING TORQUE



PART#	DESCRIPTION	PKG QTY	CTN QTY	CTN WT.
3432	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" FOR 5/8" RODS - 6000 FT. LB.	6	1	58
3433	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" FOR 3/4" & 1" RODS - 6000 FT. LB.	6	1	62
3434	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 5/8" RODS - 6000 FT. LB.	4	1	50
3435	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	4	1	60
3436	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 5/8" RODS - 6000 FT. LB.	2	1	33
3437	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	2	1	40
3438	14" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	2	1	44
3439	15" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-3/8" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	2	1	52

1-1/2" SQ. SOLID HUB: 6000 FT. LB. MAXIMUM WORKING TORQUE



PART#	DESCRIPTION	PKG QTY	CTN QTY	CTN WT.
3473	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 5/8" RODS - 6000 FT. LB.	6	1	60
3474	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	6	1	60
3475	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 5/8" RODS - 6000 FT. LB.	4	1	54
3476	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	4	1	64
3478	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	2	1	36
3479	14" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 6000 FT. LB.	2	1	42
3480	15" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" OR 1" RODS - 6000 FT. LB.	2	1	48



Earth Anchor TELECOMMUNICATION Hardware Catalog

June 08, 2026



1-1/2" SQ. SOLID HUB: 7000 FT. LB. MAXIMUM WORKING TORQUE

PART#	DESCRIPTION	PKG QTY	CTN QTY	CTN WT.
3450	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 7000 FT. LB.	6	1	59
3451	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 7000 FT. LB.	4	1	52
3452	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 7000 FT. LB.	2	1	35



1-1/2" SQ. SOLID HUB: 8000 FT. LB. MAXIMUM WORKING TORQUE

PART#	DESCRIPTION	PKG QTY	CTN QTY	CTN WT.
3460	8" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 8000 FT. LB.	6	1	62
3461	10" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 8000 FT. LB.	4	1	52
3462	12" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 8000 FT. LB.	2	1	35
3463	15" SINGLE SOLID SQUARE HUB HELIX POWER DRIVEN ANCHOR 1-1/2" HUB FOR 3/4" & 1" RODS - 8000 FT. LB.	2	1	40